

Stock Collection

Natural Wool Collection

GRAPHICS TUFTED | GT1350

Product Specifications

| | | | |
|------------------------|--|-------------------------|------------------|
| Quality Name | GT1350 | | |
| Construction | Graphics Tufted | | |
| Description | Cut Pile Tufted Carpet | | |
| Fibre Content | 80% Wool / 20% Nylon | | |
| Country of Origin | U.K. | | |
| | Metric | Imperial | Tolerance |
| Yarn Count | R560/2 | 2/55's | |
| Machine Gauge | 31.5/dm | 8 per inch | |
| Pile Height above Back | 7.0mm | 0.28" | ±10% |
| Total Carpet Thickness | 9.0mm | 0.39" | ±10% |
| Total Pile Weight | 1350g/m ² | 39.83oz/yd ² | ±10% |
| Total Carpet Weight | 2020g/m ² | 59.59oz/yd ² | ±10% |
| Product Width | 4.00m | | ±1.25% |
| Backing Materials | Woven Polyester, EVA (ethylene vinyl acetate), evobac; 100% recycled PET-Post consumer plastic | | |

Performance Classification

| | |
|------------------------|--------------------------------|
| Performance BS EN 1307 | Class 33; Heavy Commercial Use |
| Luxury Class | LC4 |

E.U Flammability Classification

| | |
|---------------|--------|
| BS EN 13501-1 | Cfl-s1 |
|---------------|--------|

Colour Fastness

| | |
|------------|-----------|
| Light | Minimum 5 |
| Shampooing | Minimum 4 |
| Water | Minimum 4 |
| Rubbing | Minimum 4 |

Installation Methods

Carpet should be installed in accordance with Newhey installation specifications. This may vary subject to type of installation and site conditions. For guidance and advice please contact a Newhey representative.

Maintenance

Proper maintenance and care is critical to the long term performance of any carpet and should be written in to the specification of a project. For guidance and advice please contact a Newhey representative.

Newhey Carpets reserve the right to change specification and construction materials due to raw material shortages or for the purpose of product improvements. All specifications are subject to normal manufacturing tolerances. Dye lots may vary from batch to batch.

