

#### Stock Collection

# Tierra

## GRAPHICS TUFTED | GT1250

#### **Product Specifications**

 Quality Name
 GT1250

 Construction
 Graphics Tufted

 Description
 Cut Pile Tufted Carpet

 Fibre Content
 80% wool / 20% nylon

 Country of Origin
 U.K.

Metric Imperial Tolerance Yarn Count R560/2 2/55's Machine Gauge 31.5/dm 8 per inch Pile Height above Back 7.0mm 0.28" ±10% 0.39" ±10% **Total Carpet Thickness** 9.0mm 1250g/m<sup>2</sup> 36.88oz/yd2 ±10% **Total Pile Weight Total Carpet Weight** 56.64oz/yd2 ±10% 1920g/m<sup>2</sup> Product Width ±1.25% 4.00m

Backing Materials Woven Polyester, EVA (ethylene vinyl acetate), evobac; 100% recycled PET-

Post consumer plastic

### Performance Classification

Performance BS EN 1307 Class 23/32; Heavy Domestic General Commercial Use

Luxury Class LC3

#### Moth Treatment

Ecolan moth repellent (Environmentally Friendly)

# E.U Flammability Classification

BS EN 13501-1 Cfl-s1

## Colour Fastness

Light Minimum 5
Shampooing Minimum 4
Water Minimum 4
Rubbing Minimum 4

#### Installation Methods

Carpet should be installed in accordance with Newhey installation specifications. This may vary subject to type of installation and site conditions. For guidance and advice please contact a Newhey representative.

#### Maintenance

Proper maintenance and care is critical to the long term performance of any carpet and should be written in to the specification of a project. For guidance and advice please contact a Newhey representative.

Newhey Carpets reserve the right to change specification and construction materials due to raw material shortages or for the purpose of product improvements. All specifications are subject to normal manufacturing tolerances. Dye lots may vary from batch to batch.









